DIELECTRIC BOOTS



Power Generation Power Distribution Construction Transport **Telecommunications**

An electrically insulating dielectric boot with an integral steel toe cap and vulcanized rubber sole for superior slip resistance. The Respirex Dielectric boot provides protection of up to 20kV over the complete boot for over 8 hours, and 35kV over the sole for 3 minutes.

Boot Shaft

- · Yellow dielectric compound shaft
- · 200 Joule Epoxy coated Steel toe cap to EN ISO 20345
- Seamless construction
- · Kick off lug
- Extra shin protection
- · Adjustable height
- · Ankle guard
- · Non-wicking knitted nylon lining
- · Comfort insole (removable and machine washable)
- · REACH Compliant

Boot Sole

- · Blue vulcanized rubber sole for maximum grip %30 better than a conventional safety boot sole
- Slip resistance twice that required by SATRA TM144 standards
- Cleated outsole for maximum grip
- · Two to three times the wear resistance of conventional soles
- Fuel and oil resistant
- · Greater cut resistance than conventional soles
- Resistance to hot contact 60 seconds 300°C.
- Energy absorbing tunnel system conforms to EN 20345 E
- Cold insulation to EN ISO 20345

Care

Machine washable at up to 40°C

· Shelf life of over 10 years

Electrical Protection

20 kV.....8 hours no damage Complete boot:

5 kV.....<5mA Leakage current

Sole: 35 kV.....3 minutes no damage

Certification

Safety Footwear EN ISO 20345:2011

- SB E CI HRO SRC FO EN 50321:2018 Class 2

Electrically Insulating Footwear Dielectric Footwear **ASTM F1117**

Personal Protective Equipment PPE Regulation (EU) 425/2016

Sizes

UK	3	4	5	6	7	8	9	10	11	12	13	14	15
EU	35	36	37	39	41	42	43	44	45	46	47	49	50
US	4	5	6	7	8	9	10	11	12	13	14	15	16





WorkMaster™ is a division of Respirex International Limited Unit F, Kingsfield Business Centre, Philanthropic Road, Redhill, Surrey, RH4 1DP, United Kingdom

