

DIELECTRIC MAXI OVERBOOTS



workMaster™
by RESPIREX

Power Generation

Power Distribution

Construction

Telecommunications

Transport

An electrically insulating dielectric overboot approved to current European standards with a vulcanized rubber sole for superior slip resistance. The Respirex dielectric boot provides protection of up to **20kV** over the complete boot for over three minutes.



17 kV
Maximum Working
Voltage

Boot Shaft

- Ingenious rear entry design ensures the boot is quick and easy to fit and remove
- Ideal for personnel who have to continually enter and exit hazardous areas
- Yellow dielectric compound shaft
- Seamless construction
- Kick off lug
- REACH Compliant

Boot Sole

- Blue vulcanized rubber sole for maximum grip - 30% better than a conventional safety boot sole
- Slip resistance performance twice that required by EN 13287 SRA and SATRA TM144 standards
- Two to three times the wear resistance of conventional soles
- Fuel and oil resistant
- Greater cut resistance than conventional soles
- Resistance to hot contact 60 seconds 300°C.

Care

- Machine washable at up to 40°C
- Shelf life of over 10 years

Electrical Protection

Complete boot: 20 kV.....3 Minutes, no damage
5 kV.....Less than 5mA Leakage current

Certification

Safety Footwear	EN ISO 20347:2012 - I HRO SRA FO
Electrically Insulating Footwear	EN 50321:1999 Class 0 pr EN 50321:2013 Class 1
Dielectric Footwear	ASTM F1117
Personal Protective Equipment	PPE DIR 89/686/EEC

Sizes

	Medium	Large	Extra-Large
UK	6 - 8	9 - 11	12 - 14
EU	39 - 42	43 - 45	46 - 49
US	7 - 9	10 - 12	13 - 15



LOTO SAFETY REQUISITES TRADING L.L.C.

Tel: +971-4-4539779 Fax: +971-4-4539778 DUBAI - UAE

E-mail: info@lotosafetyproducts.com

CALL US TODAY: +971-50-5843270

www.lotosafetyproducts.com